COMMONWEALTH OF KENTUCKY

Natural Resources & Environmental Protection Cabinet Department for Environmental Protection DEP7007M METAL CLEANING DEGREASERS

DIVISION FOR AIR QUALITY

Depending on the type of degreasing operation, complete the corresponding section *only*.

Emissions Point #______

If more than one degreaser is located at this plant, make additional copies of this form, as necessary.

Emission Unit #____

	SECTION I COLD CLEANING DEGREASER ONLY
1)	Manufacturer Model No Serial No
	Inside Dimensions of Tank (ft.): Width Length Depth
	Freeboard height: feet
	Date Tank Installed
	Type: Dip Tank Spray Sink
	Maximum Operation: Hours/day Days/week Weeks/year
2)	Solvent Type (Name and Manufacturer):
3)	Equipment Design: Is the degreaser equipped with:
	Tank Cover: Yes No Agitation: Yes No
	Drainage Board: _Yes _No If yes, check the type:
	If yes, check the type:InternalExternal Pumped Air
	Drainage Return (if external): Yes No Mechanical Ultrasonic
	Is solvent sprayed? Yes No Heating: Yes No
	Spray Pressurepsi If heated, give temperature: °F
4)	OPERATING PROCEDURE Can degreaser be closed during degreaser operation? Yes No
	Is degreaser cover closed when degreaser is not in use? Yes No
	Are parts dry before removal from drying rack? Yes No
	How are waste solvent and sludge disposed of?
5)	INDICATE THE TYPE OF CONTROL DEVICES (if any): _ Refrigerated _ Carbon Adsorption _ Water Spray _ Freeboard Ratio = 0.7 Other (specify):

DEP7007M

Continued)

	SECTION II OPEN TOP VAPOR DEGREASER ONLY
6)	Manufacturer: Model No Serial No
ŕ	Inside Dimension of Tank (ft.): Width Length Depth
	Date Installed: Freeboard Height feet
	Is Solvent Sprayed? Yes No Spray pressure psi
	Maximum Operation: Hours/day Days/week Weeks/year
7)	Solvent: Type (Name and Manufacturer):
	Maximum Amount Used: gallons/hour gallons/year (Attach MSDS for each solvent used)
8)	Indicate The Types Of Safety Switches The Degreaser Is Equipped With:
	 Condenser flow switch and thermostat (to shut off sump heat if condenser coolant either is not circulating or too warm). Spray safety switch (to shut off spray pump if the vapor level drops more than four inches below the bottom condenser coil in order to prevent spraying above the vapor level).
	Vapor level control thermostat (to shut off sump heat if the vapor zone rises above the design level).
9)	Type of Vapor Level Controls:
	Condensing Coil Chilled Water or Refrigerant None
10)	Method of Heating the Degreaser:
	Gas Electric Steam Rating: BTU/hr., or KW
11)	Type of Cleaning Action:
	Sonic Immersion in Liquid Mechanical Mixing Vapor Condensation
	Spray Other
12)	Tank Cover: Automatic Manual None
13)	How are Waste Solvent and Sludge Disposed of?
14)	In Heads The Towns of Control Device (if your)
14)	Indicate The Type of Control Device (if any):
	Refrigerated Chiller Carbon Adsorption Enclosed Design Freeboard Ratio = 0.75 Other (specify):
15)	A. Are The Parts To Be Degreased Moved in and Out at a Vertical Speed of Less Than 11 ft./Min _Yes _No B. What is The Exhaust Air Flow? Cfm

DEP7007M

Continued)

	SECTION III CONVEYORIZED DEGREASER ONLY
16)	Manufacturer: Model No Serial No
	Inside Dimension of Tank (ft.): Width Length Depth
	Date Installed: Freeboard Height feet
	Is Solvent Sprayed? Yes No Spray pressure psi
	Type: Cold Solvent Vapor Degreasing
	Work Load Design Specifications
	Maximum Operation: Hours/day Days/week Weeks/year
17)	Equipment Design: Does the degreaser have: Drying tunnel Tumbling or rotating baskets
	Is the tank covered when not in use? Yes No
18)	Indicate The Types Of Safety Switches The Degreaser Is Equipped With:
	Condenser flow switch and thermostat (to shut off sump heat if condenser coolant either is not circulating or too warm).
	Spray safety switch (to shut off spray pump if the vapor level drops more than four inches below the bottom condenser coil in order to prevent spraying above the vapor level).
	Vapor level control thermostat (to shut off sump heat if the vapor zone rises above the design level).
19)	Method of Heating the Degreaser:
	Maximum Amount Used: Gallons/hour Gallons/year
	Maximum Volatility at 100°F: mm Hg
20)	Indicate the Type of Control Device(s):
	Refrigerated Chiller Carbon Adsorption Other (specify):
21)	Operating Parameters:
	Actual conveyor speed ft/min.
	Maximum vertical conveyor speed at exit or entrance of the degreaser ft/min.
	Flow rate of exhaust cfm
	Temperature of solvent bath °F or °C
22)	How are Waste Solvent, Sludge From the Still and Solvent From the Adsorber Disposed of?